

The DEBO Step®

Installation Instructions for DEBO Step **Model 40101**
Fits 04-11 Nissan Titan, with Factory hitch.



DEBO Step Installed, Stowed Position



DEBO Step Extended for use with tailgate down.

Tools required for Installation: 17mm box end wrench or socket to fit bolt heads.

Parts List: (1) DEBO Step, (1) Instruction sheet

FOR YOUR SAFETY! The mounting bracket slide is wire tied to the step bar. **DO NOT** Remove until your step is mounted to the vehicle. If unlatched, the bracket is free to move, and could cause injury. SEE Step 5.



This picture shows 2004-2009 Titans

This picture shows 2010-2011 Titans

Step 1. The DEBO Step mounts on the driver side of the truck, using two of the existing M12 hitch frame mounting holes as shown at left.

Remove the 2 bolts from the vehicle.

The bolts have weld nuts on top of the frame which will stay in place.



Step 2. Position The DEBO Step mounting bracket in place as shown at left.

Re-install the M12 bolts through the bracket, and into the weld nuts on the frame, as shown at left.

Step 3. Before tightening bolts all the way, align step bar with frame of truck for proper location.

Step 4. Tighten both bolts securely!

Step 5. Remove the wire tie.

Your DEBO Step is ready for use.

NOTE: Your DEBO Step will be at a slight angle downward when fully extended, due to the clearance between the step bar and the slide guide end plates. This design feature is what makes The DEBO Step™ self locating!

Use your DEBO Step in any position! The step bar rotates slightly until it contacts the slide bracket at the points of contact. These "**contact pressure points**" resulting from the slight angle are what keeps the step from sliding when in use in any position. Remember this feature when operating your DEBO Step.

TO OPERATE: Using one hand, at the same time, lift the yellow latch knob "up" with the fingers to unlatch and hold, push "down" lightly with the thumb on the step pad to align the step bar with the slide bracket, and "pull" out to any desired position. Pull out part way for use with the tailgate up. Pull out to the fully extended position for use with the tailgate down.

To store, simply slide the step in. No need to touch the latch knob. Just "lift" or push "down" lightly (depending on the position of the step) on the step pad to align the step bar and the slide bracket, and "push" in until the latch engages, as simple as closing a door! Remember, the secret to moving the step bar *freely* is to release the "**contact pressure points**" by aligning the step bar with the slide bracket.

It's really quite easy. After just a couple of tries, you will find:

It's as simple as closing a door!

DO NOT EXCEED! Weight limit 400 pounds



Debo Step
Distributed By Diversified Products USA
2724 Otter Creek Crt.
Las Vegas, NV 89117
Toll Free 866-587-4707